

EFI VUTEk GS3250LX Pro

Production-level LED UV printer designed to lower your total cost of ownership

With "cool cure" LED technology and increased productivity, you will be able to produce jobs more efficiently and faster than ever before, offer more applications, and lower your operating costs.



Specifications

Media/Handling

- Handles rigid and sheeted media up to 126.5 in. (3.2 m) wide and up to 2 in. (5.08 cm) thick
- Multi-roll capable (two 60" rolls)
- Optional Heavy-Duty Unwinder available for heavy roll-to-roll shops
- Optional Extension Table with casters to attach to printer or as a workstation
- Optional Small Depth Extension Table for use with small boards/ panels and multiple fence stops

Productivity

- Fast-5: 2,400 ft²/hr (223 m²/hr)
 - Production up to 60 – 4'x8' (1.2m x 2.4m) boards per hour
- Eight-color plus white: 1,200 ft²/hr (111 m²/hr)
 - Production up to 32 – 4'x8' (1.2m x 2.4m) boards per hour

Environmental considerations

- Compressed Air: 100-150 psi maximum at 12 cf/m—dry air only (not included)
- Fully enclosed design for operator safety and environmental considerations
- Temperature: 68° F to 86° F (20° C to 30° C)
- Humidity: 40% to 80% (noncondensing)
- Machine weight: 6,700 lbs. (3,039 kg)
- Height: 66" (167.6 cm)
- Width: 248" (630 cm)
- Depth: 63" (160 cm) without tables
- Electrical: 3-Phase, 20 amps @ 200–230 volt supply or 10 amp @400-460 volt supply

Genuine EFI Inks

- Supplied in 5.0-liter containers
- Expanded gamut CMYK pigments for world-class pantone matching
- EFI pigment dispersions ensure optimized size and concentration for best-in-class ink stability

Enhanced Service Program (ESP)

- EFI's industry-leading service and support program for your printer, Fiery proServer hardware and Fiery XF software
- Thirteen months of Essential coverage, with 24-business-hour (three-business-day) response
- Eligible for upgrade to:
- Critical: Providing eight-business-hour (one-business-day) response
- ProActive: Providing 16-business-hour (two-business-day) response

Fiery digital front end

- [EFI Fiery® proServer Premium](#)